



Product data sheet

RUGGED ELITE SM 5W-40

LUBCON RUGGED ELITE SM 5W-40 is a fully synthetic motor oil of exceptional quality; delivering extreme performance developed for all gasoline, diesel, and LPG fuelled engines working under heavy load and temperature conditions and has been specially developed to withstand high pressure and temperature conditions.

LUBCON RUGGED ELITE SM 5W-40 has outstanding thermo-oxidative stability, effectively preventing the formation of sludge, resulting in a prolonged engine life.

LUBCON RUGGED ELITE SM 5W-40 reduces internal friction and fuel consumption. The optimized dispersant and detergent properties of the oil effectively prevent deposit formation on the internal engine parts, giving a longer life to the engine.

LUBCON RUGGED ELITE SM 5W-40 exceeds the requirements of most modern European, North American and Japanese car manufacturers.

Specification:

Exceeds the Performance Level: ACEA A3/B4, API SM/CI-4

| Property: | Test Method: | Typical Values: |
|--|---------------------|-------------------------|
| SAE Viscosity Grade | SAE J300 | 5W-40 |
| Relative Density @ 15 ⁰ C | ASTM D 4052 | 0.857 |
| Kinematic Viscosity @ 40 ⁰ C | ASTM D445 | 85mm ² /s |
| Kinematic Viscosity @ 100 ⁰ C | ASTM D445 | 14.4 mm ² /s |
| Viscosity Index | ASTM D2270 | 177 |
| Flash Point | ASTM D92 | >200 ⁰ C |
| Pour Point | ASTM D97 | -33 ⁰ C |
| Total Base Number | ASTM D974 | 15mgKOH/g |

PACKAGING

1L, 6L and 200L