



Product data sheet

DIESELUBE SYN 10W40

DIESELUBE SYN 10W40 is a full synthetic technology lubricant suitable for diesel heavy duty applications with excellent performance allowing smooth and cold starts.

DIESELUBE SYN 10W40 is produced with a unique formulation which prevents deposit formation and protects the engine against soot build-up for prolonged engine life and to maximize engine durability.

DIESELUBE SYN 10W40 is designed to provide enhanced protection against oil oxidation, viscosity loss due to shear and oil aeration as well as protection against catalyst poisoning, particulate filter blocking, engine wear, piston deposits, degradation of low and high- temperature properties and soot.

Specifications:

Exceeds Performance Level: API CF

Property	Test Method:	Typical Values:
SAE Viscosity Grade	SAE J300	10W/40
Relative Density @ 15 ⁰ C	ASTM D4052	0.880
Kinematic Viscosity @ 40 ⁰ C	ASTM D445	82.4 mm ² /s
Kinematic Viscosity @ 100 ⁰ C	ASTM D445	14.5 mm ² /s
Viscosity Index	ASTM D2270	184
Flash Point	ASTM D92	230 ⁰ C
Pour Point	ASTM D97	-39 ⁰ C
Total Base Number	ASTM D974	16 mgKOH/g

PACKAGING
4L, 5L, 25L and 20



Product data sheet

NANO DIESELUBE 15W40

NANO DIESELUBE 15W40 is a heavy duty formulation for diesel engine oil developed in association with VMP AUTO LLC which combines top quality mineral base oil with the best nano additives to create the oil that gives superior protection.

BENEFIT

- Preserves full power and performance.
- Reduces fleet maintenance costs.
- Eliminates unstable compression.
- Eliminates vibrations and noise.
- Reduces fuel consumption.
- Eliminate smoke.
- Superior engine cleanliness.

Specifications:

Exceeds Performance Level: API CF_4

Property	Test Method:	Typical Values:
SAE Viscosity Grade	SAE J300	15W/40
Relative Density @ 15°C	ASTM D4052	0.880
Kinematic Viscosity @ 40°C	ASTM D445	110 mm ² /s
Kinematic Viscosity @ 100°C	ASTM D445	14.5 mm ² /s
Viscosity Index	ASTM D2270	134
Flash Point	ASTM D92	230°C
Pour Point	ASTM D97	-390°C
Total Base Number	ASTM D974	10 mgKOH/g

PACKAGING

5L, 25L and 200L