



Product data sheet

HYDRAL AW68

LUBCON HYDRAL is a premium quality high performance anti wear hydraulic oil with a very high viscosity index developed for use in high pressure hydraulic systems operating under varying temperatures where small viscosity changes with fluctuating temperatures are preferred. **LUBCON HYDRAL** is designed for use in variety of industrial applications such as machine tools, presses, and in plants that transmit power hydraulically.

Specifications:

Exceeds Performance Level: API: Sperry Vickers 35VQ25, DIN 51525

| Property | Test Method: | Typical Values: |
|--|---------------------|------------------------|
| SAE Viscosity Grade | SAE J300 | |
| Relative Density @ 15 ⁰ C | ASTM D4052 | 0.885 |
| Kinematic Viscosity @ 40 ⁰ C | ASTM D445 | 68 mm ² /s |
| Kinematic Viscosity @ 100 ⁰ C | ASTM D445 | 8.8 mm ² /s |
| Viscosity Index | ASTM D2270 | 102 |
| Flash Point | ASTM D92 | 230 ⁰ C |
| Pour Point | ASTM D97 | -24 ⁰ C |

PACKAGING
25L, 200L and Bulk



Product data sheet

ATF DEXTRON

III ATF DEXTRON III is designed for use in passenger cars, light and heavy duty truck automatic transmissions, power steering units, rotary vane and screw type compressors, hydraulic systems and manual transmissions where this type of fluid is specified.

Specifications:

Performance Level: General Motors Dextron III

| Property | Test Method: | Typical Values: |
|--|---------------------|------------------------|
| Relative Density @ 15 ⁰ C | ASTM D4052 | 0.872 |
| Kinematic Viscosity @ 40 ⁰ C | ASTM D445 | 34.8mm ² /s |
| Kinematic Viscosity @ 100 ⁰ C | ASTM D445 | 7.2 mm ² /s |
| Viscosity Index | ASTM D2270 | 150 |
| Pour Point | ASTM D97 | -40 |
| Flash Point | ASTM D92 | 215 ⁰ C |
| Total Base Number | ASTM 974 | 3.2 |

PACKAGING

1/2L, 1L and 200L