



Product data sheet

2T SUPER

LUBCON 2T SUPER is a premium quality low ash detergent oil developed specifically for two stroke engines with small horse power. It could be used as separate lubrication or premix lubricant/fuel application.

LUBCON 2T SUPER has anti-wear properties and mixes perfectly with petrol and a low carbon formation. It prevents spark plug fouling recommended for lubrication of air-cooled two stroke engines of motorcycles, scooters, mopeds and two or three wheeled vehicles.

LUBCON 2T SUPER is suitable for use in small out board engines of lawnmowers, small tractors, chain saws and other horticultural machines. It is to be used in a fuel/oil ratio of about 25 to 1 or else in the proportions recommended by the engine manufacturers.

Specifications:

Exceeds Performance Level: API: TA, TB and TC

Property:	Test Method:	Typical Values:
SAE Viscosity Grade	SAE J300	SAE 20
Relative Density @ 15 ⁰ C	ASTM D4052	0.888
Kinematic Viscosity @ 40 ⁰ C	ASTM D445	70mm ² /s
Kinematic Viscosity @ 100 ⁰ C	ASTM D445	8.9 mm ² /s
Viscosity Index	ASTM D2270	95
Flash Point	ASTM D92	230 ⁰ C
Pour Point	ASTM D97	-27 ⁰ C
Base Number	ASTM D974	1.7mgKOH/g

PACKAGING

1L and 200L