

Product data sheet LUBCON 4T

**LUBCON 4T** is a high quality multi-grade engine oil made from highly refined mineral base oils and high quality performance additives used for 4-stroke motorcycles. It has very good temperature properties and excellent resistance against foaming, corrosion and engine wearing. **LUBCON 4T** offers outstanding thermo-oxidative stability, fuel economy performance and very low volatility resulting in a prolonged engine life. It provides extended drain-time and greater engine efficiency.

**LUBCON 4T** is recommended for a wide range of high powered 4-stroke motorcycles.

## **Specifications:**

Exceeds Performance Level: API: SF, JASO MA

| Property                                | Test Method: | Typical Values:            |
|---|--------------|----------------------------|
| SAE Viscosity Grade                     | SAE J300     | 20W-50                     |
| Relative Density @ 15 <sup>0</sup> C    | ASTM D4052   | 0.870                      |
| Kinematic Viscosity @ 40 <sup>o</sup> C | ASTM D445    | $118$ mm $^2$ /s           |
| Kinematic Viscosity @ 100°C             | ASTM D445    | $18 \text{ mm}^2/\text{s}$ |
| Viscosity Index                         | ASTM D2270   | 120                        |
| Flash Point                             | ASTM D92     | 246°C                      |
| Total Base Number                       | ASTM D974    | 4.2 mgKOH/g                |

PACKAGING 1L, 200L and Bulk