



Product data sheet

**SUPER XV**

**LUBCON SUPER XV** is a superior quality multi-grade engine oil multi-grade motor oil, blended from highly refined paraffinic base stocks and sophisticated additive package.

**LUBCON SUPER XV** is produced with a unique formulation which prevents deposit formation and protects the engine against soot build-up for prolonged engine life and to maximize engine durability.

**LUBCON SUPER XV** advanced chemistry formulation reduces friction, fuel consumption, extended drain-time and engine component wear.

**LUBCON SUPER XV** is designed for naturally aspirated and turbocharged car engines. It is particularly suited for high performance petrol, diesel and turbocharged passenger cars, four-wheel drive vehicles, and light vans.

### **Specifications:**

**Exceeds Performance Level:** US. Military MIL-L-46152D, API: SJ/CF

<b>Property:</b>	<b>Test Method:</b>	<b>Typical Values:</b>	<b>Typical Values:</b>
<b>SAE Viscosity Grade</b>	SAE J300	<b>15W-40</b>	<b>20W-50</b>
<b>Relative Density @ 15°C</b>	ASTM D4052	0.883	0.889
<b>Kinematic Viscosity @ 40°C</b>	ASTM D445	100mm <sup>2</sup> /s	118mm <sup>2</sup> /s
<b>Kinematic Viscosity @ 100°C</b>	ASTM D445	14.5 mm <sup>2</sup> /s	18 mm <sup>2</sup> /s
<b>Viscosity Index</b>	ASTM D2270	120	120
<b>Flash Point</b>	ASTM D92	230°C	246°C
<b>Pour Point</b>	ASTM D97	-30°C	-27°C
<b>Total Base Number</b>	ASTM D974	9.0mgKOH/g	9.0mgKOH/g

### PACKAGING

1L, 4L, 25L and 200L