

## Product data sheet

## **MULTI G. DIESEL**

**LUBCON MULTI G. DIESEL** is a multi-purpose heavy duty engine oil of high quality designed to meet the requirements of turbo-charged and naturally aspirated diesel engines.

**LUBCON MULTI G. DIESEL** is produced with a unique formulation which prevents deposit formation and protects the engine against soot build-up for prolonged engine life and to maximize engine durability.

**LUBCON MULTI G. DIESEL** is formulated for use in passenger cars, light truck construction, offhighway equipments and long distance trucks that require premium heavy duty engine oil

## **Specifications:**

## Exceeds Performance Level: CH4/CF-4/CF/CH4/SG, MIL-L-2104E

Property	Test Method:	<b>Typical Values:</b>
SAE Viscosity Grade	SAE J300	15W/40
<b>Relative Density</b> @ 15 <sup>0</sup> C	ASTM D4052	0.880
Kinematic Viscosity @ 40°C	ASTM D445	$109.2 \text{ mm}^2/\text{s}$
Kinematic Viscosity @ 100 <sup>0</sup> C	ASTM D445	$15 \text{ mm}^2/\text{s}$
Viscosity Index	ASTM D2270	143
Flash Point	ASTM D92	230 <sup>0</sup> C
Pour Point	ASTM D97	-27 <sup>0</sup> C
Total Base Number	ASTM D974	11 mgKOH/g

PACKAGING 4L, 5L, 25L and 200L

www.lubconinternational.com