



Product data sheet

PERFORMA XV

LUBCON PERFORMA XV is a high quality mono-grade oil recommended for both petrol and diesel engines operating under moderate to severe service condition.

LUBCON PERFORMA XV provides excellent chemical stability that prevents piston ring sticking and minimizes fuel and oil consumption.

LUBCON PERFORMA XV has detergent dispersant qualities, suppress sludge and vanish deposition, keeping engine perfectly clean.

LUBCON PERFORMA XV provides excellent anti-wear, and anti-corrosion and anti-rust protection for engines with reduction in emissions.

LUBCON PERFORMA XV is suitable for turbocharged passenger cars, pickups, light vans, four-wheel drive vehicles, including those using the most advanced modern technology.

Specifications:

Exceeds Performance Level: US. Army MIL-L-46152B, API: SF/CD

Property	Test Method:	Typical Values:	Typical Values:
SAE Viscosity Grade	SAE J300	XV40	XV50
Relative Density @ 15 ⁰ C	ASTM D4052	0.892	0.895
Kinematic Viscosity @ 40 ⁰ C	ASTM D445	155mm ² /s	233mm ² /s
Kinematic Viscosity @ 100 ⁰ C	ASTM D445	15 mm ² /s	19.6 mm ² /s
Viscosity Index	ASTM D2270	96	96
Flash Point	ASTM D92	240 ⁰ C	236 ⁰ C
Pour Point	ASTM D97	-15 ⁰ C	-15 ⁰ C
Total Base Number	ASTM D974	7.0mgKOH/g	6.2mgKOH/g

PACKAGING

5L, 200L and Bulk