



Product data sheet

SUPER OUTBOARD

LUBCON SUPER OUTBOARD is a superior quality ash-less outboard oil specially formulated for use in high-powered two-stroke outboard engines at a fuel/oil ratio of up to 50:1.

LUBCON SUPER OUTBOARD has been formulated with carefully selected additives in mineral base stocks, to provide excellent detergency, dispersancy and anti-wear performance.

LUBCON SUPER OUTBOARD is easy to mix and forms stable mixtures with gasoline also at lower temperatures. It provides resistance to plug fouling and provides excellent protection against wear, corrosion and high temperature ring sticking and scuffing.

LUBCON SUPER OUTBOARD is suitable for air-cooled two-cycle engines such as motorcycles and mopeds. It's also suitable for high powered 2-cycle water cooled outboard engines requiring the quality specification.

Specifications:

Exceeds the Performance Level: API: TC W3; BIA TC W

Property	Test Method:	Typical Values:
Relative Density @ 15 ⁰ C	ASTM D1298	0.890
Kinematic Viscosity @ 40 ⁰ C	ASTM D445	48 mm ² /s
Kinematic Viscosity @ 100 ⁰ C	ASTM D445	7.5 mm ² /s
Viscosity Index	ASTM D2270	120
Flash Point	ASTM D92	230 ⁰ C
Pour Point	ASTM D97	-30 ⁰ C
TBN (mgKOH/g)	ASTM D978	9.0

PACKAGING

1L and Bulk