



Product Data Sheet

ULTRA XT

LUBCON ULTRA XT is a premium heavy duty mono-grade oil blended from high quality base oil and additives primarily for naturally aspirated diesel engine operating under moderate to severe conditions. **LUBCON ULTRA XT** possesses good petrol engine performance and is therefore suitable for mixed fleets operating both diesel and petrol engine vehicles.

LUBCON ULTRA XT has good level of detergency, which provides excellent protection against engine deposits at both low and high temperatures thereby keeping the engine clean.

LUBCON ULTRA XT provides protection against corrosion and oil thickening caused by high temperature induced oxidation. It has foam inhibitor that dissipates air bubbles trapped in the oil, thereby ensuring that an oil film always protects moving surfaces.

Specifications:

Exceeds Performance Level: API: CF/SF, CAT T02, ALLISON C3

Property	Test Method:	Typical Values:	Typical values
SAE Viscosity Grade	SAE	40	50
Relative Density @ 15°C	ASTM D4052	0.895	0.900
Kinematic Viscosity @ 40°C	ASTM D445	115mm ² /s	220 mm ² /s
Kinematic Viscosity @ 100°C	ASTM D445	15.5 mm ² /s	20.0 mm ² /s
Viscosity Index	ASTM D2270	96	96
Flash Point	ASTM D92	230°C	245°C
Pour Point	ASTM D97	-18°C	-18°C
Total Base Number	ASTM D974	6.4mgKOH/g	6.4mgKOH/g
Sulphated ash	ASTM D874	0.9	0.9

PACKAGING

1L, 5L and 200L