



LUBCON UNIVERSAL TRACTORLUBE is recommended for transmissions, hydraulic, final drives and power steering system in agricultural and industrial tractors and similar equipments.

LUBCON UNIVERSAL TRACTORLUBE is a high quality multi functional extreme pressure fluid formulated with high quality base stocks resulting in improved oxidation resistant, viscosity retention and cold flow properties.

LUBCON UNIVERSAL TRACTORLUBE is a balanced formulation that provides excellent corrosion protection and oil oxidation stability at all service temperature.

SPECIFICATIONS:

Exceeds Performance Level: API: GL- 4. John Deere: Quatrol JDM J20A/J20C

VCE: WB 101. Allison (ATD) C-3 (UTD)

ALLISON C-4

Massey Ferguson: (CMSM1141,CMS M1143)

Ford M2C86B/C

CNH: MAT 3525 (“134-D” fluid

Caterpillar to -2

BENEFITS

- Maximum protection against wear and corrosion
- Good anti-chatter in wet brake systems
- Excellent oxidation stability
- Compatibility with seals and elastomer materials in tractors
- Low foaming

Property	Test Method:	Typical Values:
SAE Viscosity Grade	SAE J300	10W/30
Relative Density @ 15°C	ASTM D4052	0.868
Kinematic Viscosity @ 40°C	ASTM D445	65mm ² /s
Kinematic Viscosity @ 100°C	ASTM D445	10.6 mm ² /s
Viscosity Index	ASTM D2270	153
Flash Point	ASTM D92	224°C
Pour Point	ASTM D97	-39°C

PACKAGING: 4L, 25L, 200L and Bulk